

Get 1 TODAY!

CSQ® | Analytics

| Commitment | Satisfaction | Quality |

pH Meter

BOECO PORTABLE PH/ORP/TEMP METER MODEL PT-380

ref: BG5190380



- Simultaneous displays pH or mV and temperature.
- Convenient calibration with automatic buffer recognition of European and US buffer sets. Calibration data is stored in memory and is ready for use on power up.
- Automatic or manual temperature compensation
- Automatic lock mode and end point sensing are available to lock in stable readings.
- 50 data set reviewable memory.
- Automatic shut off function (30 minutes of non-use)
- Battery life 1000 hours
- Low battery indicator
- IP65 waterproof case

The PT-380 will be delivered incl. the following standard accessories: 1 x ATC probe 6000AST, each 1 x 100 ml BOECO Buffer solution pH 4,01, pH 7,00, 1 x 9 V battery, 1 x operating manual, 1 x carrying case

BOECO MULTIPARAMETER PH/ORP/ CONDUCTIVITY/TDS/SALINITY/RESISTIVITY/TEMP. BENCH TOP METER MODEL MBT-700

ref: BG5197700



- LCD with backlight showing pH / ORP or Conductivity / TDS / Salinity and temperature readings
- Two channel measurement allows measuring pH/ ORP and Conductivity/TDS/Salinity simultaneously
- Up to 5 point calibration for pH and one point calibration for conductivity
- Automatic or manual temperature compensation
- Automatic buffer recognition (NIST and USA)
- Bluetooth function to connect to smartphone, tablets or PC
- When the unit is connected to a bluetooth device, the user can store data into the device that meets GLP requirements.

The MBT-700 will be delivered incl. the following standard accessories: 1 x ATC probe, each 1 x 500 ml Buffer solution pH 4,01, pH 7,00 1 x AC adaptor, 1 x operating manual, 1 x flexible electrode holder

OSR PORTABLE PH METER

ref: OSR-PH01



- High accuracy, Backlit screen
- 3 points automatic calibration
- Replaceable pH electrode & automatic temperature compensation, test result be more precise
- ATC: 0-60°C
- Working voltage: 4*1.5V AAA battery
- Working condition: 0-40°C, RH<85%

OSR DIGITAL PH PEN

ref: OSR-PHPEN22



- High accuracy
- Water proof
- Replaceable pH electrode
- Data hold function
- Automatic calibration
- Automatic shutoff
- Test range: 0.01-14.00pH, 0-50 °C
- Resolution: 0.01pH, 0.1 °C

METERS - TABLE TOP

ref: 616.12.001



- Featured with microprocessor based design and rugged housing with splash proof keyboard.
- Microprocessor based large LCD display enables fast and accurate measurements.
- Automatic calibration enables fast measuring cycles.
- Easy replacement of electrode and the type of the electrode would be recognised automatically and shown on the display during insertion.
- Can measure and display (depending on model) pH & mV & temperature & conductivity & TDS & salt & dissolved oxygen in seconds.
- The large backlight LCD displays pH or mV or conductivity or TDS or salt or dissolved oxygen and temperature simultaneously.
- Offers a switchable temperature selection of °C or °F.
- Featured with an automatic temperature compensation (ATC).
- Stores maximum and minimum measured values in memory. Memory function can keep and recall up to 150 data.
- ORP probe is optional. Cat. No. 616.11.109.

METERS - TABLE TOP

ref: 616.11.001



- Featured with microprocessor based design and rugged housing with splash proof keyboard.
- Microprocessor based large LCD display enables fast and accurate measurements.
- Automatic calibration enables fast measuring cycles.
- Easy replacement of electrode and the type of the electrode would be recognised automatically and shown on the display during insertion.
- Offers a switchable temperature selection of °C or °F.
- Featured with an automatic temperature compensation (ATC).
- Stores maximum and minimum measured values in memory. Memory function can keep and recall up to 150 data.
- ORP probe is optional. Cat. No. 616.11.109.

Get 1 TODAY!

CSQ® | Analytics

| Commitment | Satisfaction | Quality |

pH Meter

METER - PORTABLE - PH & MV & TEMPERATURE MEASUREMENT

ref: 616.01.001



- Offers an economical solution for measuring pH & mV and temperature. Simple to calibrate by one keyboard.
- Easy to replace electrode. The new electrode will be recognised automatically and shown at the display.
- Ergonomic, lightweight and waterproof (which can even float on water) housing enables perfect outdoor practice.
- Measured values are shown by a microprocessor based large LCD display.
- Stores maximum and minimum measured values in memory.
- Offers a switchable temperature selection of °C or °F.
- Featured with a low battery and energy consumption indicator.
- Automatic switch-off function closes the circuit after 10 minutes of non use.
- Supplied in a carrying case, with instruction manual and calibration standard set.

METER - PORTABLE - PH & MV & TEMPERATURE & CONDUCTIVITY & TDS & SALT MEASUREMENT

ref: 616.02.002



- Featured with automatic temperature compensation (ATC) . Offers a switchable temperature selection of °C or °F.
- Easy to replace electrode. The new electrode will be recognised automatically and shown at the display.
- Automatic switch-off function closes the circuit after 10 minutes of non use.
- Offers an economical solution for measuring pH & mV & temperature & conductivity & TDS & salt with one single electrode.
- Ergonomic, lightweight and waterproof (which can even float on water) housing enables perfect outdoor practice.
- Simple to calibrate by one keyboard. Memory function stores and recalls different measurements.
- Microprocessor based large LCD displays show the measured values and the temperature simultaneously. For mV measurement 616.02.102 should be used.

ODEON - THE POLYVALENT HANDHELD DEVICE



- Handheld numerical devices dedicated to water quality control on the field or in the laboratory.
- Optical Sensors (Oxygen, Turbidity) and electrochemical (pH, ORP, temperature, conductivity)
- Memory : 8 MB (up to more than 100,000 records)
- Power supply : 4 x 1.5V AA • Options: • Rechargeable Battery • Power. External 12 V
- Battery life : 145-190 hours depending on the configuration
- Communication : USB
- Dimensions & weight : 196.5 x 121 x 46 mm, 400g
- Protection : IP 67

- Operating temperature, humidity : - 25 to + 50 ° C, 0-70%
- Storage temperature, humidity : - 25 to + 65 ° C, 0-80%
- Display : LCD 4 «240 x 320 pixel display with adjustable backlighting
- Connectors : • 1 connector: ODEON OPEN ONE • 2 connectors: ODEON OPEN X



OPEN ONE (1 Sensor input)
ref: NC-POR-C-00101



OPEN X (2 Sensor inputs)
ref: NC-POR-C-00129

PHEHT: PH, ORP & TEMPERATURE



- The PHEHT sensor has been designed to perform under hard conditions from pure mountains water with conductivity as low as 20 µS/cm, lakes and rivers (100 – 2000 µS/cm), seawater with conductivities of 50 mS/cm and to wastewater with conductivity higher than 200 mS/cm.
- Technical specifications Measures pH
Measure principle : Combined electrode (pH/ref) : special glass, Ag/AgCl ref. Gelled electrolyte (KCl)
Range : 0 – 14 pH; Resolution : 0,01 pH; Accuracy : ± 0,1 pH
- Technical specifications Measures ORP
Measure principle : Combined electrode (ORP/reference) : Platinum tip, Ag/AgCl AgAgCl. Gelled reference (KCl)
Range - 1000 to + 1000 mV; Resolution 0,1 mV; Accuracy ± 2 mV
- Technical specifications Measures Temperature
Technology : NTC
Range : 0,00 °C to + 50,00°C; Resolution : 0,01 °C; Accuracy : ± 0,5 °C

Follow us on:



Distributed by,
CSQ Analytics Sdn Bhd (956471-X)
Tel.: +606 - 651 9118
Email: info@csqanalytics.com
Website: <https://csqanalytics.com>